


# Public Address Speakers

## L-PJP20A

### Projection Loudspeaker

- Multi-Purpose cone speaker that ensures powerful and intelligible audio performance
- Stylish and unobtrusive design
- High-impact, fire-resistant ABS enclosure
- Completely water resistant
- Easy installation and cost effective
- UL60065 and RoHS compliant



Equipped with high-linearity, anti-fatigue rubber, the bass audio performance is distortion-free due to prolonged low frequency operation. The projection design is intended for use in public address applications such as corridors, shopping aisles, etc., and the sound projector has provision inside for mounting an optional line/loudspeaker supervision board. It is both UL60065 and RoHS compliant.

#### WARRANTY

2 Years

#### **Honeywell Security and Fire**

12 Clintonville Road Northford, CT 06472, USA Tel:+1.800.323.4576 www.honeywell.com



### **Technical Specifications**

#### **Electrical**

Max power	30 W
Rated power	20 W
Power tapping	20 W/10 W
Sound pressure level at 20 W /1 W (1m, 200 Hz~15 kHz)	111 dB/91 dB
Effective frequency response range (-10 dB)	150 Hz ~ 15 kHz
Dispersion angle (1 kHz/-6 dB)	120°
Rated input voltage	70 V
Rated impedance	245Ω/490Ω
Connection	Cable

#### Mechanical

Dimensions	Ø180 mm x 230 mm
Weight	2.1 kg (4.63 lbs)
Color	White (RAL9003)
Speaker size	5"

#### Environmental

Operating temperature	-25°C to + 55°C (-13°F to 131°F)
Storage temperature	-40°C to +70°C (-40°F to 158°F)
Relative humidity	<95%

**Note:** Honeywell reserves the right, without notification, to make changes in product design and/or specifications.