

L-POM20A

Column Loudspeaker

- Intelligible voice and superior sound reproduction
- Robust aluminum housing
- Supplied with universal swivel bracket for easy angle adjustment
- Adapts to extreme environments
- UL60065 and RoHS compliant



This loudspeaker is a high-performance, 20 W public address column loudspeaker for outdoor use. It provides a broad frequency response range, low distortion, and a high sound pressure level. This results in the accurate and intelligible broadcast of evacuation messages, and high quality sound reproduction.

Its low-profile, white color design blends with most interiors, including hotels, conference rooms, cinemas, theme parks, factories, and exhibitions. The loudspeaker is both UL60065 and RoHS compliant.

Technical Specifications

Electrical

Max power	30 W
Rated power	20 W (10 W x 2)
Power tapping	20 W/10 W/5 W/2.5 W
Sound pressure level at 20 W/1 W (1m, 350 Hz~15 kHz)	105 dB/92 dB
Effective frequency response range (-10 dB)	250 Hz ~ 20 kHz
Dispersion angle (1 kHz/-6 dB)	160°
Rated input voltage	70 V
Rated impedance	245Ω/490Ω/980Ω/1960Ω
Connection	Fire-resistant cable

Mechanical

Dimensions	165 mm x 150 mm x 344 mm
Weight	3.75 kg (8.27 lbs)
Color	RAL9003
Speaker size	4" x 2"

Environmental

Operating temperature	-25°C to +55°C (-13°F to 131°F)
Storage temperature	-40°C to +70°C (-40°F to 158°F)
Relative humidity	<95%

Note: Honeywell reserves the right, without notification, to make changes in product design and/or specifications.

WARRANTY

2 Years

Honeywell Security and Fire

12 Clintonville Road
Northford, CT 06472, USA
Tel:+1.800.323.4576
www.honeywell.com