

## L-POM40A

### Column Loudspeaker

- Intelligible voice and superior sound reproduction
- Robust aluminum housing
- Supplied with universal swivel bracket for easy angle adjustment
- Adapts to extreme environments
- UL60065 and RoHS compliant



This loudspeaker is a high-performance, 40 W public address column loudspeaker for outdoor use. It provides a broad frequency response range, low distortion, and a high sound pressure level. This results in the accurate and intelligible broadcast of evacuation messages, and high-quality sound reproduction.

Its low-profile, white color design blends with most interiors in hotels, conference rooms, cinemas, theme parks, factories, and exhibitions. The loudspeaker is both UL60065 and RoHS compliant.

### Technical Specifications

#### Electrical

Max power	60 W
Rated power	40 W (10 W x 4)
Power tapping	40 W/20 W/10 W/5 W
Sound pressure level at 40W /1 W (1m, 200 Hz-15 kHz)	110 dB/94 dB
Effective frequency response range (-10 dB)	150 Hz ~ 18 kHz
Dispersion angle (1 kHz/-6 dB)	150°
Rated input voltage	70 V
Rated impedance	122.5Ω/245Ω/490Ω/980Ω
Connection	Fire-resistant cable

#### Mechanical

Dimensions	165 mm x 150 mm x 568 mm
Weight	5.75 kg (12.68 lbs)
Color	RAL9003
Speaker size	4" x4"

#### Environmental

Operating temperature	-25°C to + 55°C (-13°F to 131°F)
Storage temperature	-40°C to +70°C (-40°F to 158°F)
Relative humidity	<95%

**Note:** Honeywell reserves the right, without notification, to make changes in product design and/or specifications.

### WARRANTY

2 Years

#### Honeywell Security and Fire

12 Clintonville Road  
Northford, CT 06472, USA  
Tel:+1.800.323.4576  
www.honeywell.com