

# L-PHP15A

## Horn Loudspeaker

- Low profile appearance
- Superior voice reproduction effect
- Water and dust proof, IP66 compliant
- Easy for installation
- International safety standards compliant
- UL60065 and RoHS compliant



L-PHP15A is a 15W horn loudspeaker. Its low profile appearance and white cover makes it blend easily into many outdoor environments.

In addition to excellent voice reproduction and sound transmission effect, the loudspeaker is water and dust protected, making it ideal for noisy and spacious outdoor applications, such as sports fields, parks, exhibition halls, factories and train stations etc.

The horn loudspeaker is supplied with strong adjustable mounting bracket, enabling the operator to complete the installation at ease.

### Technical Specifications

#### Electrical

Max power	25 W
Rated power	15 W
Power tapping	15 W/7.5 W
Sound pressure level at 1.5 W / 1 W (1m, 350 Hz~7 kHz)	114 dB/102 dB
Effective frequency response range (-10 dB)	400 Hz ~ 6 kHz
Dispersion angle (1 kHz/-6 dB)	140°
Line input	70V
Rated impedance	327Ω / 653Ω
Connection	Flexible wire

#### Mechanical

Dimensions	225 mm x 165 mm x 165 mm
Weight	1.38 kg (7.05 lbs)
Color	White (RAL9010)

#### Environmental

Operating temperature	-25°C to + 55°C (-13°F to 131°F)
Storage temperature	-40°C to +70°C (-40°F to 158°F)
Relative humidity	<95%

**Note:** Honeywell reserves the right, without notification, to make changes in product design and/or specifications.

## WARRANTY

2 Years

### Honeywell Security and Fire

12 Clintonville Road  
Northford, CT 06472, USA  
Tel: +1.800.323.4576  
www.honeywell.com